

Trygg hot dip galvanized



QR Code

Teknisk data

Varenr	Type	Dimensjon(d x l x b)	Vekt(kg/m)	Bevisbelastning (kN)	Bruddbel (kN)
115090	HLL	9-8 mm - 57x16mm, lengde av 280m	1,4	40	82
115100	KL	10-8 mm - 30x14mm, lengde av 200m	2,3	50	100
115110	HLL	11-8 mm - 66x18mm, lengde av 200m	2,1	61	122
115131	KL	13-8 mm - 39x17mm, lengde av 150m	3,4	84,5	169
115132	HL	13-8 mm - 50x18mm, lengde av 150m	3	85	170
115130	HLL	13-8 mm - 81x22mm, lengde av 150m	2,7	85	170
115160	KL	16-8 mm - 48x22mm, lengde av 100m	5,7	129	257
115162	HL	16-8 mm - 65x29mm, lengde av 100m	5,1	128,5	257
115161	LL	16-8 mm - 100x26mm, lengde av 100m	4,3	129	257
115190	KL	19-8 mm - 57x26mm, lengde av 75m	8	181,5	363



2,56

3,1

4,32

4,32

4,32

6,56

6,56

6,56

9,24

115191	HL	19-8 mm - 75x32mm, lengde av 75m	7,1	181,5	363	9,24
115192	LL	19-8 mm - 100x28mm, lengde av 75m	6,5	182	363	9,24
115200	KL	20-8 mm - 60x26mm, lengde av 55m	8,5	201	402	10,24
115220	KL	22-8 mm - 66x30mm, lengde av 55m	11	243,5	487	12,4
115221	HL	22-8 mm - 88x30mm, lengde av 55m	9,4	243,5	487	12,4
115222	LL	22-8 mm - 120x32mm, lengde av 55m	8,5	244	487	12,4
115251	KL	25-8 mm - 75x33mm, lengde av 50m	14,5	314	628	16,02
115250	LL	25-8 mm - 140x41mm, lengde av 50m	11	314	628	16,02
115280	LL	28-8 mm - 150x39mm, lengde av 30m	14	394	788	20,08
115320	LL	32-8 mm - 170x44mm, lengde av 30m	19	447	1029	26,24

d = tykkelse på kjettingtråd, l = innvendig lengde, b = innvendig bredde HLL / LL
- lang leddkjede HL - midtleddkjede KL - kortlenkkjede

Trygg hot dip galvanized



Produktbeskrivelse

The hot dip galvanizing is performed in steel tub with a zinc bath holding only 450°C not to reduce the strength more than necessary. At the outlet the chain is continuously moving to prevent the links from being glued together when the zinc layer is hardening. A special ash filter scrubs the surface to keep it smooth.