

# NORSE 450

QR Code

## Teknisk data

Max pulling capacity / empty drum: 45 kN, 10 116 lbf (4,0 tons)

Max pulling capacity / full drum: 20 kN, 4 496 lbf (2,0 tons)

Number of drums: 1

Wire rope, theoretical capacity: 230 ft x 3/8, 187 ft x 3/8 2 in

Recommended wire rope length: 164 ft x 3/8 2 in

Pulling speed at 540 rpm: 2,2 – 4,8 ft/s

Ratio: 1 : 5,2

Necessary power input: 32,5 kW

Braking power: 56,3 kN, 12 657 lbf

Controls: Standard cord operation

Clutch: Replaceable friction pads

Brake: Ratchet brake

Mounting: 3-point hitch

PTO input, distance from ground: 20 in, (50 cm)

Height/ Width/ Depth: 76/ 60/ 22 in, (192/ 151/ 55 cm)

Weight (without wire rope): 573 lb, (260 kg)



# NORSE 450

logo

## Produktbeskrivelse

Powerful and versatile all-round winch for farmers and woodland owners. This winch is designed with a hinged butt plate for better ability to skid over rough terrain and carry the timber over stumps and rocks. Simple and easy to operate. Two position adjustable haul in block with a standard high pulling point. The winch is operated with a cord from the tractor seat, or at a safe distance to the side. Long coil distance between top block and drum gives a good distribution of wire rope on the drum. Ideal for tractors from 40 - 75 hp.